

CN80

Rugged Mobile Computer

Logistics, warehouse, and field mobility organizations alike are transitioning from devices built on Windows® to devices built on Android™ and from keypad-centric devices to full touchscreens. But many legacy applications have not yet been updated for this new touch-centric world and for many use cases, keys remain essential for data capture.

Fortunately, there's one ultra-rugged mobile computer that helps bridge the gap. The CN80 mobile computer offers both a large touchscreen and a choice of numeric or QWERTY keypad, allowing users to pick the best input method for their environment today, and also be ready for the touch-centric applications of the future.

Built on the Mobility Edge™ platform, the CN80 mobile computer offers an integrated, repeatable, and scalable approach based on a common hardware and software platform – unleashing customers from constraints faced today around integration and inflexible technologies without sacrificing enterprise security, reliability, performance, or management features.

Juggling multiple devices across the enterprise introduces time- and cost-intensive complexities for Enterprise IT to manage and maintain. The Mobility Edge platform enables customers to accelerate provisioning, certification, and deployment across the enterprise. The CN80 mobile computer offers an extended product lifecycle across five generations of Android to maximize return on customer investment and provide a lower overall TCO. It's validated by Android Enterprise Recommended, a Google-led initiative that helps businesses confidently select, deploy, and manage the Android devices and services best suited to their enterprise needs.

The ultra-rugged CN80 mobile computer features a fast processor, advanced network connectivity, and enhanced 1D/2D scanning plus extended battery life lasting twice as long as previous generations to keep workers connected and productive throughout multiple shifts. The large, vivid, 106.7 mm (4.2 in) touchscreen display can be read easily indoors and out and used with finger, glove, or stylus – making it ideal for warehouse, cold storage, field mobility, and other challenging environments.



Built on the Honeywell Mobility Edge platform and Android, the ultra-rugged CN80 mobile computer combines touchscreen and keypad data input, real-time connectivity, and advanced data capture for industry-leading investment protection.

FEATURES AND BENEFITS



The Mobility Edge hardware platform and enterprise lifecycle tools drive an integrated, repeatable, scalable approach for accelerated and secure development, deployment, performance management, and lifecycle management.



The CN80 device provides future-proof investment protection with support for five Android generations, starting with Android 8 (O). Security updates are also available for up to two years past the last Google patch through Honeywell Sentinel.



The large touchscreen with a 23-key numeric or 40-key QWERTY keypad supports both legacy key-centric applications and newer touch applications. Keypads allow input in extremely harsh environments and optimize efficiency in all environments.



Ultra-rugged construction withstands 3.0 m (10 ft) drops to concrete and 2,000 1.0 m (3.3 ft) tumbles. IP65/IP67 ratings against dust/water spray. Cold storage and non-incendive options support operation where other products can't be used.



Enhanced 1D/2D scanning/data capture with read ranges of 0.15 m to 15.2 m (6 in to 50 ft) typically required in today's warehouses. Optional scan handle for flexibility to switch between handheld and pistol grip operations.

Honeywell

CN80 Technical Specifications

SYSTEM ARCHITECTURE

Processor: 2.2 GHz Qualcomm® Snapdragon™ 660 octa-core

Operating System: Android 8, upgradable through Android R

Memory: 3 GB/4 GB RAM, 32 GB Flash

Camera: 13.0-megapixel color camera with autofocus and advanced software features for better image quality

Audio: Speaker, T3/M3 HAC-compliant, dual microphone support with noise cancellation. PTT support and Bluetooth® wireless headset support

I/O Ports: Custom durable I/O connector with USB 3.0 signals and power input

Sensors: Ambient light sensor, proximity sensor, accelerometer, gyroscope, magnetometer, pressure sensor

Storage Expansion: User-accessible microSD card up to 512 GB (SDXC/SDHC-compliant)

Display: 106.7 mm (4.2 in) FWVGA (854 x 480) bright color LCD with backlight, outdoor viewable, optically bonded to touch panel

Touch Panel: Rugged multi-touch capacitive touch panel, optically bonded for extra durability and better sunlight visibility. Automatic detection and configuration utilizing mutual and self-capacitance modes for water rejection and use with many off-the-shelf gloves

Keypad: 40-key QWERTY keypad or 23-key numeric function keypad, plus dual side scan triggers, volume up/down, camera, power on-screen keypad

Scanning Capabilities: Honeywell N6603ER Imager (1D/2D); Honeywell EX20 Near/Far Imager (1D/2D, 0.15 m to 15.2 m [6 in to 50 ft]); Honeywell Scanning SDKs for Android

Battery: Li-Ion, 3.85 V, 5800 mAh with integrated battery diagnostics

SOFTWARE

Honeywell Power Tools and Demos

Terminal Emulator

Enterprise Browser

Application Launcher and Lockdown


Provisioning Tools

Honeywell Mobility SDKs for Android, Web, and Xamarin

Support for Third-Party MDM Solutions

WARRANTY

One-year factory warranty



For more information

www.honeywellaidc.com

www.android.com/AER

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

www.honeywell.com

ACCESSORIES

One-bay and four-bay desktop charging/com cradles

Vehicle cradles and holders

Wireless charging vehicle cradle

Snap-on communication/charging adapters

Removable scan handle, various carrying devices

MECHANICAL

Dimensions (L x W x H):

N6603ER Version: 20.4 cm x 7.8 cm x 3.32 cm (8.03 in x 3.07 in x 1.31 in)

Weight: 500 grams (17.6 oz) with battery pack

EX20 Version: 20.53 cm x 7.8 cm x 3.97 cm

(8.08 in x 3.07 in x 1.56 in)

Weight: 550 grams (19.4 oz) with battery pack

ENVIRONMENTAL

Operating Temperature:

Standard Temp Unit: -20°C to 50°C (-4°F to 122°F)

Cold Storage Unit: -30°C to 50°C (-22°F to 122°F)

Storage Temperature: -30°C to 70°C (-22°F to 158°F)

Humidity: 0 to 95% relative humidity (non-condensing)

Drop: 3 m (10 ft) to concrete at room temp per MIL-STD 810G; 1.8 m (6 ft) to concrete at -20°C to 50°C (-4°F to 122°F) temperature range; 1.6 m (5 ft) to concrete down to -30°C (-22°F)

Tumble: Exceeds 2,000 1.0 m (3.3 ft) tumbles per IEC 60068-2-32 specification

ESD: ±15 kV Air and ±8 kV Direct

Environmental Sealing: Independently certified to meet IP67 and IP65 standards for moisture and particle intrusion

WIRELESS CONNECTIVITY

WWAN: WWAN Radio (ATT/VZW/SPRINT/TMO/NA/EU) with two micro-SIM slots

- Up to 400 Mbps CAT13 LTE Downlink
- Up to 75 Mbps CAT5 LTE Uplink
 - o FDD-LTE Bands 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 19, 20, 25, 26, 28, 29
 - o TDD-LTE Bands 38, 39, 40, 41
 - o UMTS/HSPA+ (3G) Bands 1, 2, 4, 5, 6, 8, 9, 19
 - o GSM/GPRS/EDGE Quad-Band 850/900/1800/1900 MHz
 - o 1xRTT/EV-DO Bands BCO, BC1, BC10 (B26 BW)

WLAN: IEEE 802.11 a/b/g/n/ac; Wi-Fi certified 2x2 MIMO support

Additional WLAN Features: 802.11 d/e/h/i/k/l/r/w (mc with Android P)

WLAN Security: OPEN, WEP, WPA/WPA2 (Personal and Enterprise)

Supported EAP: TLS, PEAP, TTLS, PWD, FAST, LEAP CCX Version 4 certified

Bluetooth: Class 1.5 V5.0 Bluetooth and BLE

Bluetooth Profiles: HFP, PBAP, A2DP, AVRCP, OPP, SPP, GATT

NFC: Integrated Near Field Communication

Zigbee: Integrated Zigbee 3.0 radio for IoT compatibility

VoIP: Supported

VPN: IPSec V4/L2TP, PPTP

Push to Talk (PTT): Supported

GPS Supported Protocols: Simultaneous GNSS Receiver Support for GPS, GLONASS, Galileo, and BeiDou

NON-INCENDIVE VERSION

Suitable for use in Division 2 locations

Safety: cULus Listing – ISA/ANSI 12.12.01

Gases: Class I – Groups A, B, C, D

Dusts: Class II – Groups F, G

Fibers and Flying: Class III

*Max Ambient: 50°C (122°F) T6

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Mobility Edge is a trademark or registered trademark of Honeywell International Inc.

Android is a trademark or registered trademark of Google Inc.

Bluetooth is a trademark or registered trademark of Bluetooth SIG, Inc.

Qualcomm and Snapdragon are trademarks or registered trademarks of Qualcomm Incorporated.

Windows is a trademark or registered trademark of Microsoft Corporation.

All other trademarks are the property of their respective owners.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell

CN80 Data Sheet | Rev E | 10/19
© 2019 Honeywell International Inc.

دیتاتیک | ۸۸۳۱۷۷۳۴ (۰۲۱)

www.datatech.ir